

FLX-38.4-1-12MM-2216-24

LED flexible strip



FEATURES


- Various angles 120 °
- With self-adhesive tape on the back
- Made up of high quality LEDs
- Work voltage DC24V
- Cut every 25.4mm

APPLICATIONS

- Car decoration
- Architectural decorative lighting
- Archway, ceiling, bridge edge lighting
- Auditorium walkway lighting
- Signage letters backlighting
- Channel letter lighting


MECHANICAL SPECIFICATIONS

–Dimensions version 480DEL/m



Unit: mm
Cut: 25.4mm

–Connection diagram



- ① Power supply (driver)
- ② LED strips
- ③ Wires
- ④ Amplifier
- ⑤ LED controller

TECHNICAL SPECIFICATIONS

LED DIMENSIONS




SMD2216
(2.2mm x 1.6mm)

LED QTY



480DEL/m
dual line

INCREMENT



Cut every
25.4mm

VOLTAGE



24 volt

POWER



38.4W/m

PCB WIDTH



12mm

COLOR



Dual white:
2700-6500K, 3000-3200lm/m

PROTECTION TYPE



IP20

NOTICE

Before application, please make sure the power supply is in accordance to the strips.

DISCLAIMER

Due to our continued efforts to improve our documents and products, the specifications found on this document are subject to change without notice.