


SERIES ALBA

Recessed aluminum profile with trim

Once recessed, this series, with its wider trim, will make a statement in your decor. Like most LED123 products, it comes with many color, finish, wattage, lens and assembly options. Favoring better heat dissipation despite being recessed, this series will stand out for its uncompromising performance.



Description	mm	Inch
A - Width flange	74.93	2.9500
B - Width interior	41.08	1.6173
C - Width exterior	48.75	1.9193
D - Height	22.70	0.8937



FEATURES

- Modern
- Imposing
- Can be cut to your needs
- Allows continuous joint mounting
- Direct lighting
- Wide choice of lens
- Wide choice of colors and finishes
- Clear Anodized Aluminum 6063T5


APPLICATION

Regular (all purpose)

MOUNTING






PROJECTION



POWER

Type	Lumen Meter	Feet	Watt Meter	Feet
Unique white	420	128	4.8	1.5
Unique white	500	152	4.8	1.5
Unique white	840	256	9.6	2.9
Unique white	1000	305	9.6	2.9
Unique white	700	213	12.0	3.7
Unique white	1100	335	12.0	3.7
Unique white	1400	427	14.0	4.3
Unique white	1200	366	14.4	4.4
Unique white	1700	518	18.0	5.5
Unique white	1700	518	19.2	5.9
Unique white	1800	549	19.2	5.9
Unique white	3400	1036	22.0	6.7
Unique white	4000	1219	22.0	6.7
Unique white	2000	610	28.8	8.8
Unique white	2200	671	28.8	8.8
Unique white	2300	701	28.8	8.8
Variable white	750	229	9.6	2.9
Variable white	1500	457	19.2	5.9
Variable white	1680	512	19.2	5.9
Variable white	1500	457	23.0	7.0
Variable white	2000	610	23.0	7.0
Dim to warm	1800	549	23.0	7.0
Dim to warm	2300	701	26.0	7.9
RGB			8.5	2.6
RGB			14.4	4.4
RGB			17.0	5.2
RGB			20.0	6.1
RGB			20.0	6.1
RGB			28.8	8.8
RGBA			19.2	5.9
RGBA			19.2	5.9
RGBA			23.0	7.0
RGBA			30.0	9.1
RGBW			19.2	5.9
RGBW			23.0	7.0
RGBW			30.0	9.1

COLOR TEMPERATURE

Kelvin	Type
2200K	 RGB
2400K	
2700K	 RGB+ W
3000K	
3500K	 RGB+ A
4000K	
5000K	 Dim to warm 1800K - 3000K
5200K	
6000K	
6500K	 Variable white 2500K - 6000K 2700K - 6000K

GRADATION

Type
Not dimmable
Dimmable Triac
Dimmable 0-10 Volt

DIFFUSER

Type	Light diffuse	Angle
Frost	86 %	120 °
Opalin	78 %	120 °

SHAPE



LUMINAIRE COLOR





Sale sheet

31-08-2021 02:50:35

DISCLAIMER

Due to our continued efforts to improve our documents and products, the specifications found on this document are subject to change without notice.