



IES INDOOR REPORT

PHOTOMETRIC FILENAME : FLX-38.4-2-2216-24-IP20-18K LL-1750 ALU-DFR_IESNA95.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-1995
 [TEST] 01
 [TESTLAB] LED-123 LAB
 [TESTDATE] 12-15-2020
 [ISSUEDATE] XX-XXX-1995
 [NEARFIELD]
 [LAMPPOSITION] 0,0
 [OTHER] LED123
 [MANUFAC] LED123
 [LUMCAT] FLX-38.4-2-2216-24-IP20-18K
 [LUMINAIRE] LL-1750 ALU LL-1750 DFR
 [LAMPCAT] 1
 [LAMP] 2216 480LED CRI90 PCB 15MM
 [BALLAST] DC24V

CHARACTERISTICS

Lumens Per Lamp	1471.7 (1 lamp)
Total Lamp Lumens	1471.7
Luminaire Lumens	2756
Total Luminaire Efficiency	187 %
Luminaire Efficacy Rating (LER)	74
Total Luminaire Watts	37.2
Ballast Factor	1.00
CIE Type	Semi-Direct
Spacing Criterion (0-180)	1.30
Spacing Criterion (90-270)	2.12
Spacing Criterion (Diagonal)	1.44
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	1.00 m
Luminous Width (90-270)	0.02 m
Luminous Height	0.00 m



LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	39910	74792	94133
55	37490	86275	115370
65	35088	105537	150263
75	35196	143203	208400
85	46931	337008	549082

IES INDOOR REPORT

PHOTOMETRIC FILENAME : FLX-38.4-2-2216-24-IP20-18K LL-1750 ALU-DFR_IESNA95.IES

CANDELA TABULATION

	<u>0</u>	<u>30</u>	<u>60</u>	<u>90</u>	<u>120</u>	<u>150</u>	<u>180</u>	<u>210</u>	<u>240</u>	<u>270</u>
0	648.146	648.146	648.146	648.146	648.146	648.146	648.146	648.146	648.146	648.146
5	669.890	684.740	696.130	704.190	693.570	679.100	663.550	612.290	576.190	563.970
10	663.170	710.720	746.110	764.160	743.550	703.170	646.850	565.890	509.890	491.330
15	648.580	729.980	795.330	819.330	791.230	719.100	622.140	513.280	439.490	416.060
20	625.920	740.860	833.540	868.160	827.330	726.660	590.210	457.410	370.050	344.190
25	598.850	742.850	864.320	909.060	855.870	725.890	552.450	401.220	307.780	277.950
30	564.930	738.050	888.060	943.620	877.180	716.740	507.840	344.190	246.020	219.200
35	523.010	727.490	903.420	970.430	889.980	699.140	460.290	290.110	194.300	170.370
40	474.940	707.010	910.910	988.540	895.230	674.300	411.330	240.060	151.740	131.580
45	423.490	677.180	910.080	998.850	891.970	642.180	355.780	193.220	116.350	100.420
50	371.710	640.830	901.310	1000.060	880.830	607.300	301.380	151.740	88.510	76.540
55	322.690	600.260	884.930	993.020	861.500	565.890	250.500	115.970	66.880	58.750
60	270.850	554.620	861.060	977.090	834.430	517.820	201.860	84.740	49.790	44.670
65	222.530	507.330	831.300	952.960	801.410	468.420	153.410	59.580	36.800	33.660
70	178.370	457.730	784.770	899.330	762.050	416.830	112.380	40.130	26.820	26.240
75	136.700	410.620	701.760	809.410	692.030	365.440	74.620	25.660	19.520	19.460
80	99.390	364.100	612.480	765.760	575.300	320.510	41.600	16.380	15.100	16.190
85	61.380	315.330	566.210	718.140	530.500	272.700	15.680	11.390	12.930	14.020
90	37.060	267.780	542.530	649.730	505.860	225.660	5.700	9.150	11.580	12.860
95	8.770	174.020	385.660	580.670	338.560	143.550	4.540	8.130	10.430	12.420
100	5.630	130.690	371.010	508.610	330.690	92.860	3.840	7.740	10.050	12.100
105	4.990	89.540	303.740	402.180	263.550	44.800	4.290	8.060	10.180	11.780
110	5.180	26.240	194.880	259.900	161.220	3.840	4.670	8.130	10.620	11.970
115	5.250	3.460	94.140	133.310	70.980	3.200	5.060	8.320	11.010	12.290
120	5.570	3.520	29.630	50.750	17.410	3.520	5.500	8.640	11.200	12.540
125	6.080	3.840	4.800	10.820	4.350	3.840	5.950	8.900	11.330	12.670
130	6.530	4.350	4.350	3.260	4.420	4.290	6.340	9.220	11.390	12.740
135	6.850	4.800	4.480	3.580	4.610	4.740	6.780	9.470	11.460	12.800
140	7.230	5.180	4.800	3.970	4.930	5.250	7.230	9.660	11.460	12.670
145	7.620	5.700	5.250	4.480	5.310	5.820	7.620	9.730	11.460	12.540
150	8.000	6.210	5.700	5.060	5.820	6.340	7.940	9.860	11.260	12.220
155	8.260	6.660	6.270	5.630	6.340	6.850	8.260	9.860	11.070	11.900
160	8.640	7.170	6.780	6.270	6.910	7.360	8.640	9.920	10.820	11.580
165	8.900	7.680	7.420	6.980	7.420	7.870	8.960	9.790	10.430	11.140
170	9.150	8.190	8.000	7.680	8.060	8.380	9.220	9.660	10.050	10.620
175	9.340	8.640	8.640	8.450	8.700	8.830	9.410	9.470	9.600	9.980
180	9.265	9.265	9.265	9.265	9.265	9.265	9.265	9.265	9.265	9.265

Vert. Horizontal Angles

	<u>300</u>	<u>330</u>	<u>360</u>
0	648.146	648.146	648.146
5	572.220	605.820	669.890
10	507.650	563.070	663.170
15	439.870	513.980	648.580
20	372.610	461.500	625.920
25	312.260	410.240	598.850
30	251.840	356.480	564.930
35	201.410	302.660	523.010
40	158.910	253.760	474.940
45	122.430	205.180	423.490
50	93.180	162.180	371.710
55	70.460	125.180	322.690
60	52.420	91.710	270.850
65	38.530	62.850	222.530
70	26.940	43.580	178.370
75	19.260	27.900	136.700
80	13.700	17.790	99.390

IES INDOOR REPORT**PHOTOMETRIC FILENAME : FLX-38.4-2-2216-24-IP20-18K LL-1750 ALU-DFR_IESNA95.IES****CANDELA TABULATION - (Cont.)**

85	12.800	12.670	61.380
90	11.140	10.750	37.060
95	11.460	9.730	8.770
100	10.880	9.020	5.630
105	10.750	8.260	4.990
110	11.070	8.130	5.180
115	11.260	8.510	5.250
120	11.460	8.900	5.570
125	11.580	9.220	6.080
130	11.710	9.540	6.530
135	11.780	9.730	6.850
140	11.780	9.920	7.230
145	11.710	10.050	7.620
150	11.580	10.110	8.000
155	11.330	10.110	8.260
160	11.010	10.110	8.640
165	10.620	9.980	8.900
170	10.180	9.860	9.150
175	9.660	9.600	9.340
180	9.265	9.265	9.265

IES INDOOR REPORT**PHOTOMETRIC FILENAME : FLX-38.4-2-2216-24-IP20-18K LL-1750 ALU-DFR_IESNA95.IES****ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	236.36	16.10	8.60
0-30	503.83	34.20	18.30
0-40	834.64	56.70	30.30
0-60	1564.76	106.30	56.80
0-80	2200.36	149.50	79.80
0-90	2432.97	165.30	88.30
10-90	2371.81	161.20	86.10
20-40	598.28	40.70	21.70
20-50	961.57	65.30	34.90
40-70	1074.19	73.00	39.00
60-80	635.60	43.20	23.10
70-80	291.53	19.80	10.60
80-90	232.61	15.80	8.40
90-110	262.69	17.80	9.50
90-120	296.17	20.10	10.70
90-130	304.50	20.70	11.00
90-150	315.46	21.40	11.40
90-180	322.82	21.90	11.70
110-180	60.13	4.10	2.20
0-180	2755.79	187.30	100.00

Total Luminaire Efficiency = 187.30%

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	61.16
10-20	175.19
20-30	267.47
30-40	330.81
40-50	363.29
50-60	366.83
60-70	344.07
70-80	291.53
80-90	232.61
90-100	162.79
100-110	99.89
110-120	33.48
120-130	8.34
130-140	5.87
140-150	5.08
150-160	3.95
160-170	2.53
170-180	0.87

IES INDOOR REPORT

PHOTOMETRIC FILENAME : FLX-38.4-2-2216-24-IP20-18K LL-1750 ALU-DFR_IESNA95.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	218	218	218	218	210	210	210	210	196	196	196	183	183	183	171	171	171	165
1	192	180	170	160	184	174	164	156	162	154	147	150	144	138	140	135	130	124
2	172	154	138	126	165	148	134	122	138	126	116	128	119	110	119	111	104	99
3	156	133	116	102	149	128	112	99	119	106	95	111	100	90	103	94	86	81
4	142	117	99	85	135	113	96	83	105	91	79	98	86	76	91	81	72	67
5	130	104	85	72	124	100	83	70	93	79	68	87	75	65	82	71	62	57
6	119	93	75	62	114	90	73	61	84	69	59	79	66	56	74	63	54	49
7	110	84	66	54	106	81	65	53	76	62	51	71	59	49	67	56	48	43
8	103	76	59	48	98	74	58	47	69	56	46	65	53	44	62	51	42	38
9	96	70	54	43	92	68	52	42	64	50	41	60	48	39	57	46	38	34
10	90	64	49	39	86	62	48	38	59	46	37	56	44	36	53	42	34	31

IES INDOOR REPORT

PHOTOMETRIC FILENAME : FLX-38.4-2-2216-24-IP20-18K LL-1750 ALU-DFR_IESNA95.IES

UGR TABLE - CORRECTED

Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size UGR Viewed Crosswise

X=2H	Y=2H	23.9	25.4	24.4	25.9	26.5	30.4	31.9	31.0	32.5	33.1
	3H	25.8	27.2	26.4	27.8	28.4	33.8	35.2	34.3	35.7	36.4
	4H	26.6	28.0	27.2	28.5	29.2	35.4	36.7	36.0	37.3	37.9
	6H	27.4	28.6	28.0	29.2	29.9	37.2	38.4	37.7	39.0	39.6
	8H	27.7	28.9	28.3	29.5	30.2	38.1	39.3	38.7	39.9	40.6
	12H	28.0	29.2	28.6	29.8	30.4	39.3	40.4	39.9	41.0	41.7

UGR Viewed Endwise


4H	2H	25.8	27.1	26.4	27.7	28.3	31.0	32.3	31.5	32.9	33.5
	3H	28.0	29.2	28.6	29.8	30.4	34.7	35.8	35.3	36.4	37.1
	4H	29.0	30.1	29.6	30.7	31.4	36.5	37.6	37.1	38.2	38.9
	6H	30.0	30.9	30.6	31.5	32.2	38.5	39.4	39.1	40.0	40.7
	8H	30.4	31.3	31.0	31.9	32.6	39.6	40.5	40.2	41.1	41.8
	12H	30.7	31.5	31.4	32.2	32.9	40.9	41.7	41.5	42.3	43.1
8H	4H	30.7	31.6	31.3	32.2	32.9	36.9	37.7	37.5	38.4	39.1
	6H	32.0	32.7	32.6	33.4	34.1	39.1	39.9	39.8	40.5	41.3
	8H	32.6	33.3	33.2	33.9	34.7	40.4	41.1	41.1	41.8	42.5
	12H	33.1	33.7	33.8	34.4	35.2	42.0	42.6	42.6	43.3	44.1
12H	4H	31.2	32.0	31.8	32.7	33.4	36.9	37.7	37.6	38.4	39.1
	6H	32.7	33.4	33.4	34.0	34.8	39.2	39.9	39.9	40.6	41.3
	8H	33.5	34.1	34.2	34.8	35.6	40.6	41.3	41.3	41.9	42.7

Maximum UGR = 44.1

IES INDOOR REPORT

PHOTOMETRIC FILENAME : FLX-38.4-2-2216-24-IP20-18K LL-1750 ALU-DFR_IESNA95.IES

POLAR GRAPH



Maximum Candela = 1000.06 Located At Horizontal Angle = 90, Vertical Angle = 50

1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)

2 - Horizontal Cone Through Vertical Angle (50) (Through Max. Cd.)